

## WT-500 Resistant floor marking tape

### PRODUCT AND APPLICATION DESCRIPTION

Characteristic of the tape are the bevelled edges, which prevent rapid damage even under permanent load in general traffic with lift trucks or cleaning machines. The belt also has a dirt-resistant surface.

- | For smooth indoor floors
- | Suitable for pedestrians and lift trucks
- | Suitable for concrete screed smooth, EP / PU / MMA coatings and tiles



### TECHNICAL DATA

Material:	PVC
Thickness: (without Liner)	1.1 mm $\pm$ 0.1
Liner:	Paper
Surface:	Matte
Adhesive:	Acrylic
Adhesive property:	Permanent
Temperature resistance:	-20°C to +70°C
Application temperature:	$\geq$ 12°C
Available colours:	Yellow, blue, red, white, black, green, yellow/black, red/white

### MORE INFORMATION

It is possible to drive over the belt with floor conveyors. Turning and twisting on the tape with floor conveyors or similar heavy vehicles must be avoided and can lead to the destruction of the tape. To achieve optimum adhesion, the substrate must be free of release agents such as grease, oil, surfactants, dirt and dust. Store in a dry and UV-protected place at 10°C to 25°C.

#### Note

The product information listed above has been compiled to the best of our knowledge and is based on current data. The properties mentioned are typical but therefore do not constitute a specification. The information provided does not relieve the customer of his obligation to test for suitability for the intended applications and processes. All specifications are subject to change without notice. Colour variations are possible.