

TECHNICAL SHEET

| | |
|---------------|--|
| Name | HAND STRETCH FILM 17MY TRANSPARENT 500mm 2,35kg (0,22) BOX BROWN |
| Type | Polyolefin Manual Stretch Film Rolls |
| Additions | None |
| Base Material | LLD-PE |
| Density | 0,918 g/cm3 ± 5% |
| Thickness | 17 µm ± 1µm |
| Width | 500 mm ± 2% |
| Colour | Transparent |

TECHNICAL SPECIFICATION

| Update date | 28-06-2024 | | | |
|-----------------------------------|------------|----------------|-----------|-----------|
| Parameter | Units | Method | Values | Tolerance |
| MAX. TENSILE STRESS AT BREAK (MD) | % | Highlight test | < 378 | ±15% |
| GUARANTEED PRESTRETCH | % | Highlight test | 120 - 150 | ±10% |
| DART DROP IMPACT RESISTANCE** | (kg) | Highlight test | 2,50 | ±15% |
| CLING LEVEL** | (g) | Highlight test | < 33 | ±20% |

Real length of film can differ from theoretical length because due global thickness and density of the film. Colour foil has less length per kg films then transparent foil due difference of density of films. Colour foil have bigger density than transparent films.

*given values of properties have been determinate from laboratory tests conducted in certain conditions, in case of the failure to comply manufacturer's recommendations, especially about storage conditions and use of the product, the properties above may differ from the declared properties. They should be considered indicative only to simplify product selection and appropriate application. Data is not provided for warranty purposes.

**parameters determined at pre-stretch 120%

External view of the product: Transparent films without tearing, holes.

We herby certify that this product does not put in danger the life, health, working security and environmental protection.

In accordance with the applicable regulation stretch film is not classified as a dangerous product. It does not contain dangerous substances in conformity with EN- 13428 norm and heavy metals, phthalates, chlorine, Bisphenol A i S, mineral oil, tin, tantalum, tungsten, gold. Film can be subjected recoverable by material recycling (in accordance with EN 13430:2004) and recoverable in the form of energy recovery (in accordance with EN 13430:2004).

Only Stretch films brand Rewrap™ contain a minimum of 30% post-consumer regranulate (PCR) which is confirmed by a declaration for each delivery and own certificate. The rest of stretch films we sell is free of PCR Regranulate.

| | |
|---|--|
| <input type="checkbox"/> This film is suitable for direct contact for food. This film is not suitable for pharmaceutical. | <input checked="" type="checkbox"/> Film only for technical use. The film is not suitable for direct contact with food and pharmaceutical. |
| <input checked="" type="checkbox"/> The film produced by us may contain up to 30 in whole mass our post-industrial recycled (PIR). Film is free of post-consumer recycled (PCR.). We do not guarantee the amount of regranulate | <input type="checkbox"/> Film is free of Post-Industrial Recycled (PIR) and Post-Consumer Recycled (PCR.). |

Net weight : 2,35 kg
Paper core : Ø 2 inch x 520 mm x 0,22 kg
Gross weight : 2,57 kg ± 5%